

### Spirovent® Drain Microbubble™ Eliminator and Dirt Separator

Job Name:
Engineer:
Contractor:
Representative:

Tag	Model	Flow	Size	Location

**Specifications:**

Shell	Steel
Vent Head	Brass
Float	Non-Ferrous
Seal	Viton
O Ring	Viton
Skim Valve	Brass
Coalescing Medium	Copper
Ball Valve	Brass
Max. Working Pressure	150 psig
Max. Operating Temperature	270°F

**Notes:**  
Removable lower head to facilitate cleaning as required.

PS - Pipe Size	2"	2 ½"	3"	4"	5"	6"	8"	10"	12"
D (inches)	6.3	6.3	8.6	8.6	12.8	12.8	16.0	20.0	24.0
DF (inches)	11.2	11.2	13.4	13.4	18.1	18.1	22.8	28.1	33.1
H2 (inches)	25.3	25.3	31.4	31.4	41.7	41.7	51.8	67.5	79.7
h2 (inches)	10.4	10.4	13.6	13.6	18.9	18.9	24.2	32.1	38.2
LF (inches)	15.2	15.7	20.2	20.6	27.7	27.7	33.6	37.5	42.5
e (inches)	1	1	1	1	1	1	1	1	1
Weight (lbs)	107	150	202	233	325	355	686	990	1483
Rec. Flow (gpm)	45	70	95	170	260	375	625	950	1400
Model VDN---FA*	200	250	300	400	500	600	800	1000	1200

(Dimensions for reference only)

\*Flanged ASME Section VIII, Division 1 Stamped and Registered