

### Spirotrap® Drain 30", 36" Dirt Separator

|                 |
|-----------------|
| Job Name:       |
| Engineer:       |
| Contractor:     |
| Representative: |

| Tag | Model | Flow | Size | Location |
|-----|-------|------|------|----------|
|     |       |      |      |          |
|     |       |      |      |          |

**Specifications:**

|                            |          |
|----------------------------|----------|
| Shell                      | Steel    |
| Coalescing Medium          | Copper   |
| Ball Valve                 | Brass    |
| Max. Working Pressure      | 150 psig |
| Max. Operating Temperature | 270°F    |

**Notes:**  
Removable lower head to facilitate cleaning if required. Fabricated and stamped in accordance with ASME, Section VIII, Division 1 for unfired pressure vessels.

| PS - Pipe Size | 30"    | 36"    |
|----------------|--------|--------|
| D              | 60"    | 72"    |
| H              | 129"   | 154"   |
| h              | 92"    | 109"   |
| LF             | 85.2"  | 102.8" |
| hs             | 30"    | 36"    |
| e              | 2"     | 2"     |
| Weight (lbs)   | 9410   | 14590  |
| Rec. GPM       | 12,100 | 17,400 |
| Model          |        |        |
| TDN----FA      | 3000   | 3600   |

Bracket Detail

Bracket Detail