

Spirovent® Drain Microbubble™ Eliminator and Dirt Separator

Job Name:
Engineer:
Contractor:
Representative:

Tag	Model	Flow	Size	Location

Specifications:

Shell	Steel
Vent Head	Brass
Float	Non-Ferrous
Seal	Viton
O Ring	Viton
Skim Valve	Brass
Coalescing Medium	Copper
Ball Valve	Brass
Max. Working Pressure	150 psig
Max. Operating Temperature	270°F

Notes:
Removable lower head to facilitate cleaning as required.

PS - Pipe Size	14"	16"	18"	20"	24"	30"	36"
D (inches)	28	32	36	40	48	60	72
DF (inches)	35	40	44	48	57	79	81
H2 (inches)	98	110	122	134	158	194	230
h2 (inches)	43	49	55	61	73	91	109
LF (inches)	45	50	56	61.4	72	85.2	102.8
e (inches)	2	2	2	2	2	2	2
Weight (lbs)	1840	2480	3230	4690	7240	12220	19200
Rec. Flow (gpm)	1700	2200	2800	3500	5100	8000	11500
Model VDN----FA*	1400	1600	1800	2000	2400	3000	3600

(Dimensions for reference only)

*Flanged ASME Section VIII, Division 1 Stamped and Registered