


### Spirovent® Drain 14", 16", 18" Air Eliminator and Dirt Separator

Job Name:
Engineer:
Contractor:
Representative:


Tag	Model	Flow	Size	Location

	<p><b>Specifications:</b></p> <table border="1"> <tr><td>Shell</td><td>Steel</td></tr> <tr><td>Vent Head</td><td>Brass</td></tr> <tr><td>Float</td><td>Non-Ferrous</td></tr> <tr><td>Seal</td><td>Viton</td></tr> <tr><td>O Ring</td><td>Viton</td></tr> <tr><td>Skim Valve</td><td>Brass</td></tr> <tr><td>Coalescing Medium</td><td>Copper</td></tr> <tr><td>Ball Valve</td><td>Brass</td></tr> <tr><td>Max. Working Pressure</td><td>150 psig</td></tr> <tr><td>Max. Operating Temperature</td><td>270°F</td></tr> </table> <p><b>Notes:</b> Removable lower head to facilitate cleaning if required. Fabricated and stamped in accordance with ASME, Section VIII, Division 1 for unfired pressure vessels.</p>	Shell	Steel	Vent Head	Brass	Float	Non-Ferrous	Seal	Viton	O Ring	Viton	Skim Valve	Brass	Coalescing Medium	Copper	Ball Valve	Brass	Max. Working Pressure	150 psig	Max. Operating Temperature	270°F
Shell	Steel																				
Vent Head	Brass																				
Float	Non-Ferrous																				
Seal	Viton																				
O Ring	Viton																				
Skim Valve	Brass																				
Coalescing Medium	Copper																				
Ball Valve	Brass																				
Max. Working Pressure	150 psig																				
Max. Operating Temperature	270°F																				

Pipe Size	14"	16"	18"
D	28"	32"	36"
H2	98"	110"	122"
h2	43"	49"	55"
LF	45"	50"	56"
hs	20"	22"	22"
E	2"	2"	2"
Weight (lbs)	1840	2480	3230
Rec. GPM	2530	3300	4180
Model			
VDN----FA	1400	1600	1800



Bracket Detail



Bracket Detail