

### Spirovent® Dirt Microbubble™ Eliminator, Dirt Separator,

|                 |
|-----------------|
| Job Name:       |
| Engineer:       |
| Contractor:     |
| Representative: |

| Tag | Model | Flow | Size | Location |
|-----|-------|------|------|----------|
|     |       |      |      |          |
|     |       |      |      |          |

**Specifications:**

|                            |             |
|----------------------------|-------------|
| Body                       | Brass       |
| Vent Head                  | Brass       |
| Float                      | Non-Ferrous |
| Seal                       | Viton       |
| O Ring                     | Viton       |
| Coalescing Medium          | Copper      |
| Max. Working Pressure      | 150 psig    |
| Max. Operating Temperature | 270°F       |

Notes:

| Model        | Unit  | VDR100 | VDR125 | VDR150 | VDR200 |
|--------------|-------|--------|--------|--------|--------|
| Pipe Size    | inch  | 1      | 1-1/4  | 1-1/2  | 2      |
| D            | inch  | 3-1/8  | 3-1/8  | 3-1/8  | 4      |
| H2           | inch  | 14     | 14     | 14     | 17-1/4 |
| h2           | inch  | 6-3/4  | 6-3/4  | 6-3/4  | 7-3/4  |
| L            | inch  | 8-5/8  | 8-5/8  | 8-5/8  | 10-1/8 |
| e            | Inch  | 1/2    | 1/2    | 1/2    | 1/2    |
| Weight (lbs) | FT/SW | 9.0    | 9.0    | 9.0    | 14.5   |
| Rec. Flow    | GPM   | 10     | 15     | 30     | 40     |

FT – Female Threads / SW – Sweat Connection