



## Submittal Data

VDX 2-12

### Spirovent Quad® Air Eliminator, Dirt Separator, Hydraulic Separator, Low Loss Header

Job Name:  
Engineer:  
Contractor:  
Representative:

Tag	Model	Flow	Size	Location

	<p><b>Specifications:</b></p> <table border="1"> <tr> <td>Body</td> <td>Steel</td> </tr> <tr> <td>Vent Head</td> <td>Brass</td> </tr> <tr> <td>Float</td> <td>Non-Ferrous</td> </tr> <tr> <td>Seal</td> <td>Viton</td> </tr> <tr> <td>O Ring</td> <td>Viton</td> </tr> <tr> <td>Coalescing Medium</td> <td>Copper</td> </tr> <tr> <td>Max. Working Pressure</td> <td>150 psig</td> </tr> <tr> <td>Max. Operating Temperature</td> <td>270°F</td> </tr> </table> <p><b>Notes:</b></p>	Body	Steel	Vent Head	Brass	Float	Non-Ferrous	Seal	Viton	O Ring	Viton	Coalescing Medium	Copper	Max. Working Pressure	150 psig	Max. Operating Temperature	270°F
Body	Steel																
Vent Head	Brass																
Float	Non-Ferrous																
Seal	Viton																
O Ring	Viton																
Coalescing Medium	Copper																
Max. Working Pressure	150 psig																
Max. Operating Temperature	270°F																

Model	Unit	VDX200	VDX250	VDX300	VDX400	VDX500	VDX600	VDX800	VDX1000	VDX1200
Pipe Size	inch	2	2 1/2	3	4	5	6	8	10	12
D	inch	6.6	6.6	8.6	8.6	12.8	12.8	16.0	20.0	24.0
H2	inch	32.0	36.0	39.0	50.0	61.0	70.0	91.0	113.0	133.0
h2	inch	9.4	9.9	10.6	13.8	17.4	19.9	26.6	32.9	39.2
h3	inch	9.5	12.0	14.0	18.0	22.0	26.0	34.0	42.0	50.0
L (Threaded)	inch	12.0	12.0	15.0	15.0	---	---	---	---	---
LF (Flanged)	inch	15.0	15.0	20.0	20.0	26.0	26.0	32.0	36.0	42.0
Weight (lbs)	MT	56	64	106	137	---	---	---	---	---
	FA	80	96	146	197	273	323	622	978	1747
Rec. Flow	GPM	60	90	140	240	370	540	940	1470	2090

\*Flanged "FA" Models Fabricated and Stamped in accordance with ASME, Section VIII, Division 1