

### Spirotop® Air Release Valve

Job Name:
Engineer:
Contractor:
Representative:

Tag	Model	Quantity	Location

	<p><b>Specifications:</b></p> <table border="0"> <tr> <td>Body</td> <td>316 Stainless Steel</td> </tr> <tr> <td>Vent Head</td> <td>316 Stainless Steel</td> </tr> <tr> <td>Float</td> <td>Non-Ferrous</td> </tr> <tr> <td>Seal</td> <td>Viton</td> </tr> <tr> <td>O Ring</td> <td>Viton</td> </tr> <tr> <td>Max. Working Pressure</td> <td>150 psig</td> </tr> <tr> <td>Max. Operating Temperature</td> <td>270°F</td> </tr> </table> <p><u>Notes:</u></p>	Body	316 Stainless Steel	Vent Head	316 Stainless Steel	Float	Non-Ferrous	Seal	Viton	O Ring	Viton	Max. Working Pressure	150 psig	Max. Operating Temperature	270°F
Body	316 Stainless Steel														
Vent Head	316 Stainless Steel														
Float	Non-Ferrous														
Seal	Viton														
O Ring	Viton														
Max. Working Pressure	150 psig														
Max. Operating Temperature	270°F														

Pipe Size		1/2"
Thread	FPT	1/2"
D	(inches)	2 - 5/8
H	(inches)	4 - 3/8
P	(inches)	1/2"
Weight	(lbs)	2.0
Model No.		VTP050SS