

VDX-M 8-12

Spirovent Quad® Hydraulic Separator (Low Loss Header), Air Eliminator, Dirt Separator with Magnet

Job Name:
Engineer:
Contractor:
Representative:

Tag	Model	Flow	Size	Location

	<p>Specifications:</p> <table style="width: 100%; border-collapse: collapse;"> <tr><td style="border-bottom: 1px solid black;">Body</td><td style="border-bottom: 1px solid black; text-align: right;">Steel</td></tr> <tr><td style="border-bottom: 1px solid black;">Vent Head</td><td style="border-bottom: 1px solid black; text-align: right;">Brass</td></tr> <tr><td style="border-bottom: 1px solid black;">Float</td><td style="border-bottom: 1px solid black; text-align: right;">Non-Ferrous</td></tr> <tr><td style="border-bottom: 1px solid black;">Seal</td><td style="border-bottom: 1px solid black; text-align: right;">Viton</td></tr> <tr><td style="border-bottom: 1px solid black;">O Ring</td><td style="border-bottom: 1px solid black; text-align: right;">Viton</td></tr> <tr><td style="border-bottom: 1px solid black;">Coalescing Medium</td><td style="border-bottom: 1px solid black; text-align: right;">Copper</td></tr> <tr><td style="border-bottom: 1px solid black;">Magnets</td><td style="border-bottom: 1px solid black; text-align: right;">Neodymium</td></tr> <tr><td style="border-bottom: 1px solid black;">Max. Working Pressure</td><td style="border-bottom: 1px solid black; text-align: right;">150 psig</td></tr> <tr><td style="border-bottom: 1px solid black;">Max. Operating Temperature</td><td style="border-bottom: 1px solid black; text-align: right;">270°F</td></tr> </table> <p><u>Notes:</u></p>	Body	Steel	Vent Head	Brass	Float	Non-Ferrous	Seal	Viton	O Ring	Viton	Coalescing Medium	Copper	Magnets	Neodymium	Max. Working Pressure	150 psig	Max. Operating Temperature	270°F
Body	Steel																		
Vent Head	Brass																		
Float	Non-Ferrous																		
Seal	Viton																		
O Ring	Viton																		
Coalescing Medium	Copper																		
Magnets	Neodymium																		
Max. Working Pressure	150 psig																		
Max. Operating Temperature	270°F																		

DN - Pipe Size	8"	10"	12"
D (inches)	16.0	20.0	24.0
H2 (inches)	91.0	113.0	133.0
h2 (inches)	26.6	32.9	39.2
h3 (inches)	34.0	42.0	50.0
LF (inches)	32.0	36.0	42.0
e (inches)	1	1	1
x (inches)	3	3	3
y (inches)	3	3	3
Dry Weight (lbs)	642	998	1,767
Volume (gallons)	67	134	230
Rec. Flow (gpm)	940	1,470	2,090
Model			
VDX---FAM	800	1000	1200

(Dimensions for reference only)

Flanged. ASME Section VIII, Division 1 Stamped and Registered